

DATA SHEET

Impregnated Yarn

Product Specification *Impregnated hand sewing thread* **Type HN 150 white**

Item number	Coating	Basic size $\pm 10\%$
HNZ 072	<i>PTFE</i>	7.5 kg

Technical Data

Properties	Nominal value	Tolerance of the nominal value	Test method
Basis material	EC 13–408 x2 x3 S11	$\Delta S = \pm 15\%$	DIN EN 12654
Coating	PTFE unsintered		
Linear density of the coated yarn	2900 tex	$\pm 10\%$	
Diameter of the plied yarn	ca. 1.5 mm		-
Loss on ignition	15 %	$\pm 30\%$	DIN ISO 1887
Moisture	< 0.1 %	-	ISO 3344
Tensile strength	> 850 N	-	DIN EN ISO 3341
Knot strength	> 340 N		DIN 53842
Bobbin type	H8 or H9 bobbins; other format possible after arrangement		
Colour	white		

Packaging and Storage

The hand sewing thread is delivered on H8/H9-bobbins.

The H8/H9 tubes are returnable and remain property of P-D Glasseiden GmbH.

The bobbins are transport-secured packed in cardboard boxes.

Packing unit: H8/H9-bobbins → 46 or 23 bobbins

The packages should be stored in a dry room and in the supplier's original packaging.
Bobbins with impaired volume can to be enclosed in every packing unit.



Date: 05/20

Version: 02