

DATA SHEET

Impregnated Yarn

Product Specification

Beta – sewing thread

Type MNB 30

HNZ 4005	<i>PTFE</i>	<i>0.5 kg</i>
HNZ 4006	<i>PTFE</i>	<i>1,0 kg</i>
HNZ 4007	<i>PTFE/Oil</i>	<i>0,5 kg</i>
HNZ 4008	<i>PTFE/Oil</i>	<i>1,0 kg</i>

Technical Data

Properties	Nominal value	Tolerance of the nominal value	Test method
<i>Basis material</i>	<i>EC 4-33 x1 x4 Z340</i>	$\Delta Z = \pm 15\%$	<i>DIN EN 12654</i>
<i>Coating</i>	<i>PTFE</i>		-
<i>Oil (HNZ 4007, HNZ 4008)</i>	<i>13 %</i>	$\pm 20 \%$	-
<i>Linear density of the coated yarn (without Oil)</i>	<i>170 tex</i>	$\pm 8 \%$	<i>DIN EN ISO 1889</i>
<i>Diameter of the plied yarn</i>	<i>ca. 0.3 mm</i>		-
<i>Loss on ignition (without Oil)</i>	<i>18 %</i>	$\pm 20 \%$	<i>DIN ISO 1887</i>
<i>Moisture (without Oil)</i>	<i>< 0.1 %</i>	-	<i>ISO 3344</i>
<i>Tensile strength</i>	<i>> 75 N</i>	-	<i>DIN EN ISO 3341</i>
<i>Knot strength</i>	<i>> 20 N</i>		<i>DIN 53842</i>
<i>Bobbin type</i>	<i>small king bobbins 0.5 kg; big king bobbins 1.0 kg</i>		
<i>Colour</i>	<i>beige; can fade on exposure to light (especially ultraviolet light)</i>		

Packaging and Storage

The yarn for sewing machine is delivered on king bobbins.

You can receive other bobbins on enquiry.

Packing unit: 0.5 kg king bobbins → 12 or 50 bobbins

1.0 kg king bobbins → 9 bobbins

King bobbins with impaired volume can be enclosed in every packing unit.



Date: 05/20

Version: 02