



DATA SHEET

Impregnated Yarn

Product Specification*Impregnated yarn for sewing machine***Type MNZ 240-1 A+S****-preliminary-**

Item number	Coating	Basic size (without oil) $\pm 10\%$
HNZ 8300	<i>PTFE</i>	<i>0.4 kg</i>

Technical Data

Properties	Nominal value	Tolerance of the nominal value	Test method
<i>Basis material</i>	<i>Para-Aramid 44 tex</i>	-	-
<i>Coating</i>	<i>PTFE</i>		-
<i>Linear density of the coated yarn</i>	<i>230 tex</i>	$\pm 8 \%$	<i>DIN EN ISO 1889</i>
<i>Diameter of the yarn</i>	<i>ca. 0.5 mm</i>	-	-
<i>Loss on ignition</i>	<i>15 %</i>	$\pm 20 \%$	-
<i>Tensile strength</i>	<i>> 200 N</i>	$\pm 5 \%$	<i>DIN EN ISO 3341</i>
<i>Knot strength</i>	<i>> 60 N</i>	-	
<i>Twisting</i>	<i>Z 250</i>	$\pm 10 \%$	
<i>Reinforcing thread</i>	<i>3xV4A (W. Nr. 1.4401)</i>		-
<i>Bobbin type</i>	<i>small king bobbins 0.5kg</i>		

Packaging and Storage

The yarn for sewing machine is delivered on 0.5 kg bobbins.

You can receive other bobbins on enquiry.

Packing unit: 0.5 kg king bobbins → 12 or 50 bobbins

King bobbins with impaired volume can to be enclosed in every packing unit.



Date: 05/20

Version: 02



OSCHATZ-GLAS