

DATA SHEET

Impregnated Yarn

Product specification

PTFE – impregnated glassfilament yarn, sinterrd

Type P18/7-22

Article number: HZF 017

Technical Data

Properties	Nominal value	Tolerance off the nominal value	Test method
Basis material	EC7-22		DIN EN 12654
Coating	PTFE		
Linear Density of the Coated Yarn	27 tex	± 10 %	DIN EN ISO 1889
Loss on Ignition	18,0 %	± 20 %	DIN ISO 1887
Moisture	≤ 0,2 %	-	ISO 3344
Broaking Load	>12 N	± 5 %	DIN EN ISO 3341
Spool format	H8-bobbins or H9-bobbins		-
Colour	beige; can fade on exposure to light (especially ultraviolet light)		

Packaging information and storage

The glass filament yarn is delivered wound up onto bottle-shaped bobbins (flange diameter 203 mm/8.0 in., height 446 mm/17.6 in.).

The bobbins are returnable and remain property of PD-Grasseiden GmbH Oschatz.



The reels are packed certainly about transport packs in cardboards (B 120 x H 90 x T 100 cm), one cardboard box contains 46 packages.

Shipment box: 1 cardboard box/pallet. Different packages on request.

The packages should be stored in dry room and in supplier's original packaging.



Date: 05/20

Version: 02